

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072 HMIS H-0, F-1, R-0

IDENTITY (as Used on Label and List)  
LEATHER SOFT

*Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.*

**Section I**

Manufacturer's name **ROYALTONE**

Emergency Telephone Number **918-663-9666**

Address (Number, Street, City, State and ZIP Code)

**9504 East 55th Street**

Telephone Number for Information

**918-622-6677**

Tulsa, OK 74145

Date Prepared: 6/29/10

Signature of Preparer (optional)

**Section II—Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits  
Recommended

% (optional)

This product does not contain hazardous materials based on current Department of Labor regulations as we interpret them.

**Section III—Physical/Chemical Characteristics**

Boiling Point

625F

Specific Gravity (H<sub>2</sub>O = 1)

0.87

Vapor Pressure (mm Hg) below

0.0001

Melting Point

1.0

Vapor Density (AIR = 1)

10

Evaporation Rate (Butyl Acetate = 1)  
ethylether 1000x slower

Solubility in Water

form emulsion

Appearance and Odor

white liquid with little odor

**Section IV—Fire and Explosion Hazard Data**

Flash Point (Method Used)

380 COC

Flammable Limits NA

LEL UNK

UEL UNK

Extinguishing Media

water fog, CO<sub>2</sub>, dry chemical and foam

Special Fire Fighting Procedures

wear self contained breathing apparatus in confined spaces

Unusual Fire and Explosion Hazards

estimated auto ignition temperature 670F can be made to burn (flash point greater than

200F)

(Reproduce locally)

OSHA 174 Sept. 1985

**Section V—Reactivity Data**

Stability	Unstable		Conditions to Avoid
	Stable	X	Contact with strong oxidizers
Incompatibility ( <i>Materials to Avoid</i> ) strong oxidizers			
Hazardous Decomposition or Byproducts none			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	None

**Section VI—Health Hazard Data**

Route(s) of Entry	Inhalation? no	Skin? no	Ingestion? YES
Health Hazards ( <i>Acute and Chronic</i> ) <b>INGESTION: diarrhea EYE: contact causes moderate irritation and discomfort. SKIN: slight irritation</b>			
Carcinogenicity	NTP? no	IARC Monographs? no	OSHA Regulated? no
Signs and Symptoms of Exposure none			
Medical Conditions			
Generally Aggravated by Exposure none			
Emergency and First Aid Procedures			
EYES: flush with water for 15 min. call physician SKIN: wipe and wash with soap & water			
INGESTION: see a physician, induce vomiting if conscious			

**Section VII—Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material Is Released or Spilled	wash with water containing detergent or absorb with clay. Diatomaceous earth or other inert absorbent
Waste Disposal Method	drum & dump or incinerate as governed by Federal, State and Local regulations or chemical waste
Precautions to Be Taken in Handling and Storing	avoid contact with eyes
Other Precautions	Do not swallow

**Section VII—Control Measures**

Respiratory Protection ( <i>Specify Type</i> ) use adequate ventilation			
Ventilation	Local Exhaust	as needed for comfort	Special none
	Mechanical ( <i>General</i> )	no	Other none normally needed
Protective Gloves	no	Eye Protection	no
Other Protective Clothing or Equipment no			
Work/Hygienic Practices Do not ingest . Keep out of eyes and off skin.			